Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: MARINO CRISTAL

Supplier's address: CHIEF EXECUTIVE, VIA GUARDIA DEL CONSIGLIO 29, 47899 SERRAVALLE - REP. SAN MARINO, IT

Model identifier: 21590

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	GX16d		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	20	Energy efficiency class	F
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	2 050 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500
On-mode power (P_{on}), expressed in W	20,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, light-	Height: 176	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width: 112		
	Depth: 112		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[a]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,480 0,420
Parameters for LED and OLED light sources:				
R9 colour rendering index value		2	Survival factor	0,90
the lumen maintenance factor		0,96		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,50	Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[b]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	0,4

[a] '-' : not applicable;

[b] '-' : not applicable;


Relative intensity
1.0
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
250
380
480
580
680
800
Wavelength (nm)
2500K

Model placed on the Union market from 02/01/2019

EPREL registration number: 799094

https://eprel.ec.europa.eu/qr/799094

Supplier: MARINO CRISTAL S.r.l. (Manufacturer)

Website: www.marinocristal.com

Customer care service:

Name: CHIEF EXECUTIVE

Website: www.marinocristal.com

Email: marinocristal@marinocristal.com

Phone: +3780549901188

Address:
VIA GUARDIA DEL CONSIGLIO 29
47899
Italy